


B-28-2



Middle Kennebec River / Sasanoa River

Woolwich / Arrowsic


0 1,000 2,000 Feet



Printed: 4/2/2018



Source: Esri, DigitalGlobe, GeoEye, Earthstar Geographics, CNES/Airbus DS, USDA, USGS, AeroGRID, IGN, and the GIS User Community



Middle Kennebec River / Sasanoa River

Town Woolwich / Arrowsic

Port Region Casco Bay

Latitude 43° 54.503' N **Longitude** -69 48.201' W

Strategy B-28-2

NOAA Chart # 13293 **ESI Map #** 40C

EVI Map # 19

Resources At Risk

ESI Shoreline Type(s) Sheltered, impermeable rocky shores

Environmental Concerns Diadromous fish, shorebirds, rare plants

Strategy Information

Strategy Purpose To exclude oil from Sasanoa River

Work Assignment Deploy three 300' sections of boom across entrance to Sasanoa River

Staging Areas South End boat launch, Washington Street, Bath

Site Access By water

Nearest Boat Ramp South End boat launch, Washington Street, Bath

Collection Points N/A

Approx. Tidal Range (feet) 9

Max Current (knots) **Flood** **Ebb** **Source**

Special Instructions

Recommended Equipment / Resources

Length of Boom (feet) 900

Type of Boom Harbor

Recommended Equipment (Minimum)

- 4 - anchor systems: 35 lb. Danforth or equivalent and line for 3:1 scope plus tag line with buoy.
- 2 - shoreside connections
- 2 - workboats with minimum 90 hp
- 2 - boat operators
- 4 - laborers

Unless otherwise indicated, the boom length given is the distance measured on the chart. Actual length required may vary with conditions.