

# Harrington Lake Quadrangle, Maine


Surficial materials mapping by  
**Daniel B. Locke**

Digital cartography by:  
**Robert A. Johnston**

**Robert G. Marvinney**  
State Geologist

Cartographic design and editing by:  
**Robert D. Tucker**

Funding for the preparation of this map was provided in part by the  
Land Use Regulation Commission, Maine Department of Conservation.




**Maine Geological Survey**

Address: 22 State House Station, Augusta, Maine 04333  
Telephone: 207-287-2801 E-mail: mgs@maine.gov  
Home page: http://www.maine.gov/doc/nrimc/nrimc.htm

**Open-File No. 08-24**

**2008**

## Surficial Materials




### SOURCES OF INFORMATION

Materials data collected by the Maine Geological Survey Significant Sand and Gravel aquifer mapping program during the 2007 field season. Additional data sources include, but are not limited to, municipal water company records, U.S. Geological Survey Basic-Data Reports, Maine Geological Survey bedrock well database and bedrock geology maps, Maine Department of Environmental Protection site files, Maine Department of Transportation highway construction records, and the Maine Department of Human Services public water-supply well database.



Quadrangle Location

SCALE 1 : 24,000



CONTOUR INTERVAL 20 FEET



Topographic base from U.S. Geological Survey Harrington Lake quadrangle, scale 1:24,000 using standard U.S. Geological Survey topographic map symbols.

The use of industry, firm, or local government names on this map is for location purposes only and does not implicate responsibility for any present or potential effects on the natural resources.

This map shows the textures of surficial sediments in borrow pits and other surface exposures, as well as subsurface data from various sources. Where more than one textural class is present, materials are separated by commas and listed in decreasing order of abundance (e.g. s, st, cy). Individual materials may occur in distinct layers, or they may be mixed. Hyphens show the ranges of particle sizes present where their relative abundances are uncertain (e.g. st-c). Slash marks indicate superposition of materials; thicknesses are in feet (e.g. 10s/3cy). "Σ" indicates a significant stratigraphic sequence of interbedded materials. Some borrow pits and other localities may be designated by numbers that refer to descriptions in the quadrangle text. Not all symbols will necessarily be found on the map.

**GRAVEL** **g** Undifferentiated gravel, used as a general term. Can be subdivided by size as follows:

|          |                |                     |
|----------|----------------|---------------------|
| <b>b</b> | Boulder gravel | >256 mm (10")       |
| <b>c</b> | Cobble gravel  | 64-256 mm (2.5-10") |
| <b>p</b> | Pebble gravel  | 2-64 mm (0.1-2.5")  |

**MIXED UNITS** **gs** Gravelly sand (this is a special case for sand with lesser amounts of intermixed gravel, i.e. pebbly sand, cobbly sand, or bouldery sand)  
**sg** Sand and gravel (used only to describe slumped face or other site where relative abundances of sand vs. gravel are unknown).

**SAND** **s** Undifferentiated sand, used as a general term. Can be subdivided by size as follows:

|            |                  |                   |
|------------|------------------|-------------------|
| <b>vcs</b> | Very coarse sand | (1-2 mm)          |
| <b>cs</b>  | Coarse sand      | (0.5-1 mm)        |
| <b>ms</b>  | Medium sand      | (0.25-0.5 mm)     |
| <b>fs</b>  | Fine sand        | (0.125-0.25 mm)   |
| <b>vfs</b> | Very fine sand   | (0.0625-0.125 mm) |

**SILT** **st** Silt (0.002-0.0625 mm)

**CLAY** **cy** Clay (<0.002 mm)

**DIAMICTON** **d** Undifferentiated diamicton (poorly-sorted sediment in which particle sizes may range from clay to boulders). Used as a general term or subdivided as follows:

|           |                           |
|-----------|---------------------------|
| <b>dg</b> | Gravelly-matrix diamicton |
| <b>ds</b> | Sandy-matrix diamicton    |
| <b>dt</b> | Silty-matrix diamicton    |
| <b>dy</b> | Clayey-matrix diamicton   |

**Note:** Diamictons of glacial origin may be classified as one of the following varieties of till (shown on the map in parentheses):

|           |  |
|-----------|--|
| <b>t</b>  | Till, undifferentiated. Usually of late Wisconsinan age (deposited by the last glacial ice sheet).                       |
| <b>ta</b> | Ablation till. Deposited during retreat of the late Wisconsinan ice sheet. Typically sandy, stony, and not very compact. |
| <b>tl</b> | Lodgement till. Inferred to have been deposited at the base of the late Wisconsinan ice sheet. Usually very compact.     |
| <b>tf</b> | Flowtill. Deposited by slumping adjacent to glacial ice.   |
| <b>T</b>  | Variably weathered till (usually a lodgment facies) of inferred pre-late Wisconsinan age.                                |

**ORGANIC MATERIALS** **og** Organic-rich sediment (can be any organic material, including forest litter, wood, shells, etc.)  
**pt** Peat (reserved for actual fibrous peat)

**OTHER MATERIALS** **af** Artificial fill (e.g. road fills, building sites, dumps)  
**bd** Scattered boulders; interpreted as till where followed by (t)  
**rk** Bedrock (observed in pit floor, boring, or natural exposure)  
**rs** Rottenstone, disintegrated or weathered bedrock, saprolite.  
**u** Unknown (material unidentified)  
**R** Refusal (in test boring or well)  
**(f)** Fossiliferous (used to indicate fossiliferous units within a sequence).

**8s-b** Materials data from shovel hole, hand-auger-hole, natural exposure, or excavation (other than borrow pit).

**56** Depth to bedrock from well (Σ is used to indicate minimum depth to bedrock), in feet below land surface

● Bedrock well

● Drilled overburden well

■ Dug well

↓ Driven point

◆ **20fs, st** Observation well with materials data

◆ **10gs/rk** Test boring with materials data

⊗ **s-b** Borrow pit, recently active at time of mapping, with materials data.

⊗ **s-p** Borrow pit, evidently abandoned or in long disuse at time of mapping, with materials data.

⊗ Quarry

● Location of site for which a data sheet is on file at the Maine Geological Survey.

● **56** Depth to bedrock from seismic line, in feet below land surface

⊕ Bedrock outcrop

### OTHER SOURCES OF INFORMATION

- Locke, D. B. (compiler), 2008, Significant sand and gravel aquifers in the Harrington Lake 7.5' quadrangle, Maine: Maine Geological Survey, Open-File Map 08-25.
- Thompson, W. B., and Borris, H. W., Jr., 1985, Surficial geologic map of Maine: Maine Geological Survey, scale 1:500,000.