

Janet T. Mills GOVERNOR

## STATE OF MAINE

Department of Public Safety Office of State Fire Marshal 52 State House Station Augusta, ME 04333-0052

Michael Sauschuck COMMISSIONER

Joseph E. Thomas STATĖ FIRE MARSHAL

January 10, 2020

Memo

To: All Public Safety Inspectors

From: Joseph Thomas

Re: Thermal barriers over spray foam

This memo is to clarify the position of this office regarding the 15 minute thermal barrier required to be installed over spray foam insulation to separate the foam from habitable and occupiable spaces. Title 25 section 2447-B allows for ½" gypsum wallboard or equivalent to be installed to obtain this thermal barrier. At this time this office will recognize the following products as having achieved equivalency.

- Cafco TB -415 1.
- 2. Cafco TB-15
  - Flame Seal TB
- 3.
- 4. Flame Control No 60-60A
- 5. TPR 2 Fireshell F10E
- 6. TPR 2 Fireshell F 1 E
- 7. International Fireproof Technology Inc. DC 315
- 8. No-Burn Plus Thb

These products can be used if installed as per the manufactures instructions, this also includes following the foam manufactures requirements for coating their product. This list can be amended as more products are tested and evaluated. Installers shall provide property owners a certification of correct installation of these products. A copy of the cut sheet and the certification shall be kept by the owner for verification of compliance

Jøseph E. Thomas State Fire Marshal



Janet T. Mills GOVERNOR

## STATE OF MAINE

Department of Public Safety Office of State Fire Marshal 52 State House Station Augusta, ME 04333-0052 Michael Sauschuck COMMISSIONER

Joseph E. Thomas state fire marshal

January 10, 2020

To: All Public Safety Inspectors

From: Joseph E. Thomas

Re: Ignition barriers over spray foam

This memo is to clarify the position of this office regarding the installation of an ignition barrier over foam plastic insulation within an attic or crawl space where entry is made only for the service of utilities. The foam plastic insulation shall be protected against ignition by 1 1/2"thick mineral fiber insulation, ¼" plywood, particleboard,hardboard or gypsum wallboard, No. 26 gauge sheet steel or other approved material installed in such a manner that the foam plastic is not exposed. At this time this office will recognize the following products as having achieved equivalency to satisfy this requirement.

- 1. Cafco TB -415
- 2. Cafco TB-15
- 3. Flame Seal TB
- 4. Flame Control 5050A
- 5. TPR 2 Fireshell 1B
- 6. TPR 2 Fireshell F10E
- 7. TPR 2 Fireshell F1 E
- 8. International Fireproof Technology Inc. DC315
- 9. BASF Spraycoat 1920
- 10. No-Burn Plus XD
- 11. No-Burn Plus Thb
- 12. No-burn Plus

The following products can be installed in attics and crawl spaces where entry is made for the servicing of utilities without a prescriptive ignition barrier, when installed in conformance with the listing and manufactures requirements.

1. Gaco Western, Gaco One Pass F1850

- 2. Foam Lok FL2000-4G
- 3. SES 2 lb foam

These products can be used if installed as per the manufactures instructions, this also includes following the foam manufactures requirements for coating their product. This list can be amended as more products are tested and evaluated. Installers shall provide property owners a certification of correct installation of these products. A copy of the cut sheet and the certification shall be kept by the owner for verification of compliance

løseph E. Thomas State Fire Marshal