



STATE OF MAINE
DEPARTMENT OF TRANSPORTATION
16 STATE HOUSE STATION
AUGUSTA, MAINE
04333-0016

JOHN ELIAS BALDACCI

GOVERNOR

DAVID A. COLE

COMMISSIONER

April 15, 2008
Subject: **Winter Harbor, Ellsworth, Hancock**
State Project No's: 015209.00, 015761.00, 015866.00
Amendment No. 1

Dear Sir/Ms:

Please make the following change to the bid document:

In the Bid Book **REMOVE** "SPECIAL PROVISION, SECTION 403, HOT MIX ASPHALT OVERLAY", pages 127 and 128 (dated March 28, 2008) and **REPLACE** with the attached NEW "SPECIAL PROVISION, SECTION 403, HOT MIX ASPHALT OVERLAY" (2 pages) dated April 15, 2008.

Consider this change and information prior to submitting your bid on **April 16, 2008**.

Sincerely,


FOR
Scott Bickford
Contracts & Specifications Engineer



PRINTED ON RECYCLED PAPER

Winter Harbor 15209.00
 Acadia National Park
 Ellsworth-Hancock 15861.00
 Route 1
 Hancock 15866.00
 Route 1
 April 15, 2008

SPECIAL PROVISION
SECTION 403
HOT MIX ASPHALT OVERLAY

Desc. of Course	Grad. Design	Item #	Bit Cont. % of Mix	Total Thick	No. of Layers	Comp. Notes
<u>1" HMA Overlay Areas</u>						
<u>Mainline Travelways and Pull-out Areas</u>						
Wearing	9.5mm	403.210	N/A	1"	1	4,9,11,20,22
Shim	9.5mm	403.211	N/A	variable	1/more	2,4,9,11,20
<u>1 1/4" HMA Overlay Areas</u>						
<u>Mainline Travelway, Shoulders, Widening</u>						
Wearing	9.5mm	403.210	N/A	1 1/4"	1	4,9,20
Shim	9.5mm	403.211	N/A	variable	1/more	2,4,9,11,20
<u>1 1/4" HMA Overlay with 1 1/2" mill and resurfacing Areas</u>						
<u>Mainline Travelway</u>						
Wearing	9.5mm	403.210	N/A	1 1/4"	1	4,9,20
Base	12.5mm	403.213	N/A	1 3/4"	1/more	4,10,12
<u>Drives, Sidewalks, Misc.</u>						
Wearing	9.5mm	403.209	N/A	1"	1	2,3,10,11,14

COMPLEMENTARY NOTES

2. The density requirements are waived.
3. The design traffic level for mix placed shall be <0.3 million ESALS
4. The design traffic level for mix placed shall be 0.3 to <3 million ESALS. The design, verification, Quality Control, and Acceptance tests for this mix will be performed at **50 gyrations.**
9. Section 106.6 Acceptance, (2) Method C.
10. Section 106.6 Acceptance, (2) Method D.
11. The combined aggregate gradation required for this item shall be classified as a 9.5mm "**fine graded**" mixture, (using the Primary Control Sieve control point) as defined in 703.09.
12. The combined aggregate gradation required for this item shall be classified as a 9.5mm "**coarse graded**" mixture, or a 12.5mm "**fine graded**" mixture (using the Primary Control Sieve control point) as defined in 703.09.
14. A mixture meeting the requirements of section 703.09 Grading 'D', with a minimum PGAB content of 6%, and the limits of Special Provision 401, Table 9 (Drives and Sidewalks) for PGAB content and gradation may be substituted for this item. A job mix formula shall be submitted to the department for approval.

Winter Harbor 15209.00
Acadia National Park
Ellsworth-Hancock 15861.00
Route 1
Hancock 15866.00
Route 1
April 15, 2008

20. The Contractor may place the specified HMA pavement course, not to exceed 1¼ inch (30mm) compacted depth, over the full single travel lane width, for each production day. If this option is utilized the Contractor will be required to place a matching course of HMA over the adjacent section of travel lane before the end of the following calendar day. The Contractor will also be responsible for installing additional warning signage that clearly defines the centerline elevation differential hazard, as well as additional centerline delineation such as double RPM application, or temporary painted line. The Traffic Control Plan shall be amended to include this option and the additional requirements. All signs and traffic control devices will conform to Section 719.01, and Section 652, and will be installed prior to the work, at a maximum spacing of 0.50 mile [0.80 km] for the entire length of the effected roadway section. On roadways with two-way traffic, the Contractor will be required to place the specified course over the full width of the mainline traveled way being paved prior to opening the sections to weekend or holiday traffic. If this option is utilized, all additional signing, labor, traffic control devices, or incidentals will not be paid for directly, but will be considered incidental to the appropriate 403 items.
22. See Special Provision 401 – ¾ inch and 1 inch Surface Treatment for project specifics.

Tack Coat

A tack coat of emulsified asphalt, RS-1 or HFMS-1, Item 409.15 shall be applied to any existing pavement at a rate of approximately 0.025 gal/yd², and on milled pavement approximately 0.05 gal/yd² prior to placing a new course. A fog coat of emulsified asphalt shall be applied between shim /base courses and the surface course, at a rate not to exceed 0.025 gal/yd².

Tack used between layers of pavement will be paid for at the contract unit price for Item 409.15 Bituminous Tack Coat.